T20Pro GNSS Receiver



T20Pro is a high-performance GNSS receiver that provides an easy-to-use solution for users. TOKNAV T20Pro supports the original tilt compensating GNSS solution. Multi constellation and frequency tracking always guarantee a fixed solution for your job. LCD display screen can make your operation faster and easier. T20Pro built-in 5W radio allows users to have a longer working distance, up to 16KM in open areas, The durable IP68 design makes it possible to work in extreme environments.



Characteristic

Linux intelligent system

Qualcomm Cortex-A7 + Linux, the intelligent system platform, brings efficient computing and unlimited expansion of product functions to users.

Multi constellation

With its 1408 channels, T20Pro provides an excellent on board real time navigation solution with high accuracy. All GNSS signals (GPS, GLONASS, BDS, GALILEO, QZSS and SBAS) are included.



T20Pro has internal radio of adjustable power of 1W/2W/ 5W, and works as base station at 5W power. The transmission distance can reach to maximum 16KM when working in the open area.

Combined antenna

The new four in one antenna integrates GNSS, WIFI, Bluetooth and 4G, with smaller volume and better signal.

4G Modem

T20Pro has an internal 4G Modem that operates with more cellular network signals, a fast internet connection is guaranteed.

Long endurance

Built in high-capacity lithium battery ensures continuous working time of more than 20 hours under normal operation.

IP68 Design

Industrial design, solid magnesium alloy shell, in line with IP68 design requirements, safe and reliable.



Europe, North & South America
Tel & WhatsApp: +1 (323) 847-7713 (lan)
Asia, Africa & Oceania
Tel & WhatsApp: +86 139 2607 5986 (Jeffrey)





T20Pro GNSS Receiver



HARDWARE SYSTEM OS		SPECIFICATION Qualcomm Cortex-A7 Linux	REMARKS
GLONASS	L1, L2, L3		
BDS	B1I, B2I, B3I, B1C, B2a, B2b		
GALILEO	E1, E5a, E5b, E6		
QZSS	L1, L2, L5		
SBAS	L1		
GNSS	NavIC (IRNSS)*	L5*	IRNSS support in futu
	Channel	1408	
	Data format	NMEA-0183	
	Correction I / O Protocol	RTCM3.X	
	Data update frequency	20Hz(max)	
	Recapture Time	<1s	
	Cold Boot	<40s	
	Single (RMS)	Horizontal: 1.5m Vertical: 2.5m	
	DGPS(RMS)	Horizontal: 0.4m Vertical: 0.8m	
	RTK(RMS)	Horizontal: ±(8mm+1ppm) Vertical: ±(15mm+1ppm)	
POSITIONING	Time Accuracy (RMS)	20ns	
ACCURACY	Static Accuracy (RMS)	Horizontal: ±(2.5mm+0.5ppm) Vertical: ±(5mm+0.5ppm)	
	Speed Accuracy (RMS)	0.03m/s	
	Tilt compensation Accuracy(within 60°)	≤2cm	
	Bluetooth	BR+EDR+BLE	
	WIFI	802.11 b/g/n	
SYSTEM	Network	LTE FDD: B1/2/3/4/5/7/8/12/13/18/19/20/25/26/28 LTE TDD: B38/39/40/41 WCDMA: B1/2/4/5/6/8/19 GSM: B2/3/5/8	
	Data Radio	Frequency: 410~470MHz Protocol: TRIMTALK, TRIMMK3, SOUTH, TRANSEOT RF transmit power: 1W/2W/5W Air baud rate: 9600 / 19200bps	
	Storage	32GB Storage	
DISPLAY	LCD	Screen size: 1.3inch Display mode: TFT Display format: 240*RGB*240 View Angle: FULL	
	Battery	7.4V, 6500mAh	
BATTERY	Work time	More than 18 hours (Typical, Rover, GSM)	The static working mode supports continuous data collection for 26 hours
			under full power



Europe, North & South America Tel & WhatsApp: +1 (323) 847-7713 (lan)

Asia, Africa & Oceania

Tel & WhatsApp: +86 139 2607 5986 (Jeffrey)



T20Pro GNSS Receiver



	Charge	USB PD 15V/2A 5V/3A	Support fast charging adapter and adaptively and dynamically adjust charging current
	Work Temperature	-20℃~+60℃	
ENVIRONMENTAL	Storage Temperature	-40℃~+85℃	
	Shock	Withstand 1.5M pole drop	
	Protection	IP68	
	Material	Magnesium alloy main body, ABS/PC top cover	
PHYSICAL	Dimension	Φ143.5mm*90.7mm	
	Weight	≤0.90kg	
	T20Pro Device	1SET	
A FULL SET	USB power adapter	1 PCS	
A FULL SE I	Type-C to Type-C	1 PCS	
	Radio Antenna	1 PCS	

[▲] Manufacturers may update parameters at any time, please refer to the latest product information.

Equipped with electronic fence system, Toknav's product have area code restrictions. Any issue please contact Toknav or local dealers to verify the specific details.







